

GLOBAL STYLE SAFETY LIMIT SWITCHES (PLASTIC BODIED EN50047 TYPE) SND4 SERIES (SINGLE CONDUIT ENTRY)

SUNS products are safe and reliable products which are widely used in various mechanical devices.



Features

- Glass fiber reinforced plastic body
- Easily interchangeable contact block
- Galvanically separated contacts
- Screw terminals with self-lifting clamps for easy wiring
- Positive Opening of NC contacts
- 4 x 90° actuator positions
- Cable entry available: M20, PG13.5 and 1/2"NPT
- Conform to EN 50047 standard

Definitions of Operating Characteristics

OF Operating Force
RF Releasing Force
OT Overtravel
TT Total Travel
PT Pretravel
MD Movement Differential
OP Operating Position
PO Travel to Positive Opening



Specifications

Operating Speed	0.05mm-2m/sec
Operating Frequency	Mechanical: 120ops/min Electrical: 30 ops/min
Insulation Resistance	>100MΩ@500V DC
Contact Resistance	<25mΩ (initial value)
Rated Thermal Current	10A/600V AC (EN60947-5-1)
	AC15 A600 / DC13 Q300
Dielectric Strength	1000VAC for 1 min between current carrying parts 2500VAC for 1 min between non-current carrying parts
Service Life	Mechanically 1.0 x10 ⁷ (operations) Electrically 5 x10 ⁵ (operations)
Operating Temperature	-25~+80°C (-13~176°F) with no icing
Humidity	< 95%RH
Weight	50-100g
Degree of Protection	IP67

Selection Guide:

SND41	04	SP	C	-	R
Body Styles	Head Styles		Conduits		
		SP: 1NO/1NC Snap action			
		SPT: 2NO/2NC Snap action			
		SL: BBM 1NO/1NC Slow Action changeover			
		SL1: MBB 1NO/1NC Slow Action Overlapping	A: 1/2"NPT		Blank
		SL2: 2NC Slow Action	B: PG13.5		R: with Reset
		SL3: 2NO Slow Action	C: M20		
		SL4: 3NC Slow Action	D: M16		
		SL5: 3NO Slow Action	B1: PG11		
		SL6: BBM 2NC/1NO Slow Action changeover			
		SL7: MBB 2NC/1NO Slow Action Overlapping			
		SL8: BBM 2NO/1NC Slow Action changeover			
		SL9: MBB 2NO/1NC Slow Action Overlapping			

GLOBAL STYLE SAFETY LIMIT SWITCHES (PLASTIC BODIED EN50047 TYPE) SND4 SERIES (SINGLE CONDUIT ENTRY)

Available contact blocks and travel diagrams

ON OFF

Plunger type
11,12,31,32 styles


Side rotary type
04, 07, 08, 14, 18 Styles

62, 63 styles


72, 73 styles

00, 66,69 styles


SP
1NO/1NC
Snap Action




SPT
2NO/2NC
Snap Action




SL
1NO/1NC
Slow Action
(Changeover)




SL1
1NO/1NC
Slow Action
(Overlapping)




SL2
2NC
Slow Action




SL3
2NO
Slow Action




SL4
3NC
Slow Action




SL5
3NO
Slow Action




SL6
2NC/1NO
Slow Action
(Changeover)




SL7
2NC/1NO
Slow Action
(Overlapping)



SL8
1NC/2NO
Slow Action
(Changeover)




SL9
1NC/2NO
Slow Action
(Overlapping)




GLOBAL STYLE SAFETY LIMIT SWITCHES (PLASTIC BODIED EN50047 TYPE) SND4 SERIES (SINGLE CONDUIT ENTRY)

SND4111




Order Code	Contact block		
SND4111-SP- _	SP		1NO+1NC
SND4111-SL- _	SL		1NO+1NC BBM
SND4111-SL1- _	SL1		1NO+1NC MBB
SND4111-SL2- _	SL2		2NC

SND4112




Order Code	Contact block		
SND4112-SP- _	SP		1NO+1NC
SND4112-SL- _	SL		1NO+1NC BBM
SND4112-SL1- _	SL1		1NO+1NC MBB
SND4112-SL2- _	SL2		2NC

SND4172




Order Code	Contact block		
SND4172-SP- _	SP		1NO+1NC
SND4172-SL- _	SL		1NO+1NC BBM
SND4172-SL1- _	SL1		1NO+1NC MBB
SND4172-SL2- _	SL2		2NC

SND4173




Order Code	Contact block		
SND4173-SP- _	SP		1NO+1NC
SND4173-SL- _	SL		1NO+1NC BBM
SND4173-SL1- _	SL1		1NO+1NC MBB
SND4173-SL2- _	SL2		2NC

SND4162



Order Code	Contact block		
SND4162-SP- _	SP		1NO+1NC
SND4162-SL- _	SL		1NO+1NC BBM
SND4162-SL1- _	SL1		1NO+1NC MBB
SND4162-SL2- _	SL2		2NC


SND4163



Order Code	Contact block		
SND4163-SP- _	SP		1NO+1NC
SND4163-SL- _	SL		1NO+1NC BBM
SND4163-SL1- _	SL1		1NO+1NC MBB
SND4163-SL2- _	SL2		2NC


GLOBAL STYLE SAFETY LIMIT SWITCHES (PLASTIC BODIED EN50047 TYPE) SND4 SERIES (SINGLE CONDUIT ENTRY)

SND4104




Order Code	Contact block		
SND4104-SP- _	SP	→ snap action	1NO+1NC
SND4104-SL- _	SL	→ slow action	1NO+1NC BBM
SND4104-SL1- _	SL1	→ slow action	1NO+1NC MBB
SND4104-SL2- _	SL2	→ slow action	2NC

SND4107




Order Code	Contact block		
SND4107-SP- _	SP	→ snap action	1NO+1NC
SND4107-SL- _	SL	→ slow action	1NO+1NC BBM
SND4107-SL1- _	SL1	→ slow action	1NO+1NC MBB
SND4107-SL2- _	SL2	→ slow action	2NC

SND4114




Order Code	Contact block		
SND4114-SP- _	SP	→ snap action	1NO+1NC
SND4114-SL- _	SL	→ slow action	1NO+1NC BBM
SND4114-SL1- _	SL1	→ slow action	1NO+1NC MBB
SND4114-SL2- _	SL2	→ slow action	2NC

SND4108




Order Code	Contact block		
SND4108-SP- _	SP	→ snap action	1NO+1NC
SND4108-SL- _	SL	→ slow action	1NO+1NC BBM
SND4108-SL1- _	SL1	→ slow action	1NO+1NC MBB
SND4108-SL2- _	SL2	→ slow action	2NC

SND4118



Order Code	Contact block		
SND4118-SP- _	SP	→ snap action	1NO+1NC
SND4118-SL- _	SL	→ slow action	1NO+1NC BBM
SND4118-SL1- _	SL1	→ slow action	1NO+1NC MBB
SND4118-SL2- _	SL2	→ slow action	2NC


SND4118-ADJ



Order Code	Contact block		
SND4118-SP- _ADJ	SP	→ snap action	1NO+1NC
SND4118-SL- _ADJ	SL	→ slow action	1NO+1NC BBM
SND4118-SL1- _ADJ	SL1	→ slow action	1NO+1NC MBB
SND4118-SL2- _ADJ	SL2	→ slow action	2NC


GLOBAL STYLE SAFETY LIMIT SWITCHES (PLASTIC BODIED EN50047 TYPE) SND4 SERIES (SINGLE CONDUIT ENTRY)

SND4131




Order Code	Contact block		
SND4131-SP- _	SP	→ snap action	1NO+1NC
SND4131-SL- _	SL	→ slow action	1NO+1NC BBM
SND4131-SL1- _	SL1	→ slow action	1NO+1NC MBB
SND4131-SL2- _	SL2	→ slow action	2NC

SND4132




Order Code	Contact block		
SND4132-SP- _	SP	→ snap action	1NO+1NC
SND4132-SL- _	SL	→ slow action	1NO+1NC BBM
SND4132-SL1- _	SL1	→ slow action	1NO+1NC MBB
SND4132-SL2- _	SL2	→ slow action	2NC

SND4100




Order Code			
SND4100-SP- _	SP	→ snap action	1NO+1NC

SND4166




Order Code			
SND4166-SP- _	SP	→ snap action	1NO+1NC

SND4169



Order Code			
SND4169-SP- _	SP	→ snap action	1NO+1NC


SND4112-L



Order Code	Contact block		
SND4112-SP- _L	SP	→ snap action	1NO+1NC
SND4112-SL- _L	SL	→ slow action	1NO+1NC BBM
SND4112-SL1- _L	SL1	→ slow action	1NO+1NC MBB
SND4112-SL2- _L	SL2	→ slow action	2NC


GLOBAL STYLE SAFETY LIMIT SWITCHES (PLASTIC BODIED EN50047 TYPE) SND4 SERIES (SINGLE CONDUIT ENTRY WITH RESET)

SND4111-R




Order Code	Contact block			
SND4111-SP-_R	SP	→	snap action	1NO+1NC
SND4111-SL-_R	SL	→	slow action	1NO+1NC BBM
SND4111-SL1-_R	SL1	→	slow action	1NO+1NC MBB
SND4111-SL2-_R	SL2	→	slow action	2NC

SND4112-R




Order Code	Contact block			
SND4112-SP-_R	SP	→	snap action	1NO+1NC
SND4112-SL-_R	SL	→	slow action	1NO+1NC BBM
SND4112-SL1-_R	SL1	→	slow action	1NO+1NC MBB
SND4112-SL2-_R	SL2	→	slow action	2NC

SND4104-R




Order Code	Contact block			
SND4104-SP-_R	SP	→	snap action	1NO+1NC
SND4104-SL-_R	SL	→	slow action	1NO+1NC BBM
SND4104-SL1-_R	SL1	→	slow action	1NO+1NC MBB
SND4104-SL2-_R	SL2	→	slow action	2NC

SND4107-R




Order Code	Contact block			
SND4107-SP-_R	SP	→	snap action	1NO+1NC
SND4107-SL-_R	SL	→	slow action	1NO+1NC BBM
SND4107-SL1-_R	SL1	→	slow action	1NO+1NC MBB
SND4107-SL2-_R	SL2	→	slow action	2NC

SND4114-R



Order Code	Contact block			
SND4114-SP-_R	SP	→	snap action	1NO+1NC
SND4114-SL-_R	SL	→	slow action	1NO+1NC BBM
SND4114-SL1-_R	SL1	→	slow action	1NO+1NC MBB
SND4114-SL2-_R	SL2	→	slow action	2NC


SND4118-R



Order Code	Contact block			
SND4118-SP-_R	SP	→	snap action	1NO+1NC
SND4118-SL-_R	SL	→	slow action	1NO+1NC BBM
SND4118-SL1-_R	SL1	→	slow action	1NO+1NC MBB
SND4118-SL2-_R	SL2	→	slow action	2NC


GLOBAL STYLE SAFETY LIMIT SWITCHES (PLASTIC BODIED EN50047 TYPE) SND4 SERIES (SINGLE CONDUIT ENTRY WITH RESET)

SND4131-R




Order Code	Contact block		
SND4131-SP-_R	SP	→ snap action	1NO+1NC
SND4131-SL-_R	SL	→ slow action	1NO+1NC BBM
SND4131-SL1-_R	SL1	→ slow action	1NO+1NC MBB
SND4131-SL2-_R	SL2	→ slow action	2NC

SND4132-R




Order Code	Contact block		
SND4132-SP-_R	SP	→ snap action	1NO+1NC
SND4132-SL-_R	SL	→ slow action	1NO+1NC BBM
SND4132-SL1-_R	SL1	→ slow action	1NO+1NC MBB
SND4132-SL2-_R	SL2	→ slow action	2NC

SND4162-R




Order Code	Contact block		
SND4162-SP-_R	SP	→ snap action	1NO+1NC
SND4162-SL-_R	SL	→ slow action	1NO+1NC BBM
SND4162-SL1-_R	SL1	→ slow action	1NO+1NC MBB
SND4162-SL2-_R	SL2	→ slow action	2NC

SND4163-R




Order Code	Contact block		
SND4163-SP-_R	SP	→ snap action	1NO+1NC
SND4163-SL-_R	SL	→ slow action	1NO+1NC BBM
SND4163-SL1-_R	SL1	→ slow action	1NO+1NC MBB
SND4163-SL2-_R	SL2	→ slow action	2NC

SND4172-R




Order Code	Contact block		
SND4172-SP-_R	SP	→ snap action	1NO+1NC
SND4172-SL-_R	SL	→ slow action	1NO+1NC BBM
SND4172-SL1-_R	SL1	→ slow action	1NO+1NC MBB
SND4172-SL2-_R	SL2	→ slow action	2NC

SND4173-R




Order Code	Contact block		
SND4173-SP-_R	SP	→ snap action	1NO+1NC
SND4173-SL-_R	SL	→ slow action	1NO+1NC BBM
SND4173-SL1-_R	SL1	→ slow action	1NO+1NC MBB
SND4173-SL2-_R	SL2	→ slow action	2NC


SND4100-R




SND4100-SP-	-R	SP	snap action	1NO+1NC
-------------	----	----	-------------	---------



SND4166-SP-	-R	SP	snap action	1NO+1NC
-------------	----	----	-------------	---------




SND4169-SP- -R SP snap action 1NO+1NC




SND4108-SP-_R	SP		snap action	1NO+1NC	
SND4108-SL-_R	SL		slow action	1NO+1NC	BBM
SND4108-SL1-_R	SL1		slow action	1NO+1NC	MBB
SND4108-SL2-_R	SL2		slow action	2NC	

A black and white photograph of a mechanical device, likely a pressure transducer or sensor. It features a large black wheel with a central hub and a red base. A vertical metal rod is attached to the wheel, and a blue adjustment knob is visible on the side of the red base. The device is mounted on a black rectangular block.



Order Code	Contact block			
SND4118-SP- R-ADJ	SP		snap action	1NO+1NC
SND4118-SL-R-ADJ	SL		slow action	1NO+1NC BBM
SND4118-SL1-R-ADJ	SL1		slow action	1NO+1NC MBB
SND4118-SL2-R-ADJ	SL2		slow action	2NC


A red and black SCHEMATIC 12VDC solenoid valve. It features a blue handle on the left side and a brass fitting on top. The label on the front provides technical specifications and safety information.



Order Code	Contact block			
SND4112-SP-SR	SP		snap action	1NO+1NC
SND4112-SL-SR	SL		slow action	1NO+1NC
SND4112-SL1-SR	SL1		slow action	1NO+1NC
SND4112-SL2-SR	SL2		slow action	2NC


GLOBAL STYLE SAFETY LIMIT SWITCHES (PLASTIC BODIED EN50047 TYPE) SND4 SERIES (SINGLE CONDUIT ENTRY WITH RESET)

SND4107-SR




Order Code	Contact block		
SND4107-SP- _SR	SP	→ snap action	1NO+1NC
SND4107-SL- _SR	SL	→ slow action	1NO+1NC BBM
SND4107-SL1- _SR	SL1	→ slow action	1NO+1NC MBB
SND4107-SL2- _SR	SL2	→ slow action	2NC

SND4108-SR




Order Code	Contact block		
SND4108-SP- _SR	SP	→ snap action	1NO+1NC
SND4108-SL- _SR	SL	→ slow action	1NO+1NC BBM
SND4108-SL1- _SR	SL1	→ slow action	1NO+1NC MBB
SND4108-SL2- _SR	SL2	→ slow action	2NC

SND4114-SR




Order Code	Contact block		
SND4114-SP- _SR	SP	→ snap action	1NO+1NC
SND4114-SL- _SR	SL	→ slow action	1NO+1NC BBM
SND4114-SL1- _SR	SL1	→ slow action	1NO+1NC MBB
SND4114-SL2- _SR	SL2	→ slow action	2NC

SND4104-SR




Order Code	Contact block		
SND4104-SP- _SR	SP	→ snap action	1NO+1NC
SND4104-SL- _SR	SL	→ slow action	1NO+1NC BBM
SND4104-SL1- _SR	SL1	→ slow action	1NO+1NC MBB
SND4104-SL2- _SR	SL2	→ slow action	2NC

SND4118-SR-ADJ



Order Code	Contact block		
SND4118-SP- SR-ADJ	SP	→ snap action	1NO+1NC
SND4118-SL-SR-ADJ	SL	→ slow action	1NO+1NC BBM
SND4118-SL1-SR-ADJ	SL1	→ slow action	1NO+1NC MBB
SND4118-SL2-SR-ADJ	SL2	→ slow action	2NC

SND4118-SR



Order Code	Contact block		
SND4118-SP- _SR	SP	→ snap action	1NO+1NC
SND4118-SL- _SR	SL	→ slow action	1NO+1NC BBM
SND4118-SL1- _SR	SL1	→ slow action	1NO+1NC MBB
SND4118-SL2- _SR	SL2	→ slow action	2NC